

# Ready to win the race

- with innovation.



Spies Hecker – simply closer.



# Finish First with Spies Hecker.

Together the new Spies Hecker Permasolid® HS Speed Surfacer 5500 and Priomat® Reactive Pretreatment Wipes 4000 define innovation and performance for the undercoating process. We are talking racing speed with a non-stop application without intermediate flash-off times and an impressive air-drying performance with sanding after only 20-60 minutes. That fast drying comes with the winning feeling and a smooth surface that guarantees excellent gloss hold-out after top coating.



*The Priomat Reactive Pretreatment Wipes 4000 guarantee excellent adhesion and corrosion protection.*

## Priomat® Reactive Pretreatment Wipes 4000

Based on a new technology, the Priomat Reactive Pretreatment Wipes 4000 will significantly speed-up the metal pretreatment process. Pre-saturated with active ingredients, they provide adhesion and help to improve corrosion resistance for the subsequent paint process. Further advantages are:

- Reduced flash-off times compared to 2K wash primers by about 20-25 minutes (80%).
- Economical; one wipe can be used to pretreat approximately 2m<sup>2</sup>.
- Fast and easy wipe-on application, no mixing or equipment required.

Priomat Reactive Pretreatment Wipes 4000 are mandatory for pre-treatment on bare metal substrate prior to applying the Permasolid HS Speed Surfacer 5500.



# Include the **NEW** super-fast curing surfacer and pretreatment wipes in your line-up.

## Permasolid® HS Speed Surfacers 5500

High Speed Surfacers for higher throughput. The new Permasolid Speed Surfacers 5500 significantly speeds up the preparation process, saving time and energy thanks to both its application method and impressive air-drying performance.

- Air-drying time is significantly shorter compared to standard air-drying surfacers. This results in faster processing, allowing sanding from as early as 20 minutes subject to local climatic conditions.
- Using a simple 1:1 mixing ratio with Permasolid HS Speed Surfacers Hardener 3550 delivers superior drying results using various drying techniques:

| Temperature   | Time         |
|---------------|--------------|
| 20°C          | 20 – 60 mins |
| 40 – 45°C     | 10 – 15 mins |
| 60 – 65°C     | 5 – 10 mins  |
| IR Half Power | 5 – 10 mins  |

- From Speed Repair to standard panel repair, in fact any type of job, can be dried at the same time.
- Available in three colours: Grey, White and Black.



*Apply Permasolid HS Speed Surfacers 5500 continuously without intermediate flash-off as per TDS.*



*The smooth surface helps to ensure excellent gloss hold-out after top coating.*



*The new air-drying record allows sanding after just 20 minutes depending on local climatic conditions.*



## How to make an unbeatable team.

When used together, Permasolid® HS Speed Surfacer 5500 and Priomat® Reactive Pretreatment Wipes 4000 deliver benefits to bodyshops in the form of reduced process times and energy consumption, whilst maximising productivity. And, when combined with Permahyd® Hi-TEC Base Coat 480 and Permasolid HS Speed Clear Coat 8800, delivers further savings no matter the repair, climate condition or drying option available.

**Hi-TEC  
Performance**

**Speed Repair**



For more information or to watch the latest video scan the QR Code or visit [www.spieshecker.com.au/speed-5500](http://www.spieshecker.com.au/speed-5500)

**Contact us.**

**1800 292 582**  
**[www.spieshecker.com.au](http://www.spieshecker.com.au)**

An Axalta Coating Systems Brand

